

# Product datasheet

Specifications



## Mini Pragma surface enclosure - IP 40 - 3 x 12 modules - transparent door

13923

⚠ Discontinued on: 23 Jan 2021

⚠ Discontinued

### Main

|                             |                                                                                                            |
|-----------------------------|------------------------------------------------------------------------------------------------------------|
| Range                       | Mini Pragma                                                                                                |
| Product Or Component Type   | Enclosure                                                                                                  |
| Enclosure Type              | Modular enclosure                                                                                          |
| Nb Of 18 Mm Modules Per Row | 12                                                                                                         |
| Nb Of Horizontal Rows       | 3                                                                                                          |
| Provided Equipment          | 1 marking kit<br>1 insulating plug<br>2 terminal block support<br>2 earth-neutral terminal blocks 22 holes |
| Type Of Door                | Transparent                                                                                                |
| Width                       | 256 mm                                                                                                     |
| Height                      | 451 mm                                                                                                     |
| Depth                       | 96 mm                                                                                                      |

### Complementary

|                               |                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------|
| Enclosure Mounting            | Surface                                                                                    |
| 9 Mm Pitches                  | 24                                                                                         |
| Total Number Of 18 Mm Modules | 36                                                                                         |
| [In] Rated Current            | 63 A                                                                                       |
| [Ui] Rated Insulation Voltage | 690 V                                                                                      |
| Type Of Rail                  | DIN                                                                                        |
| Number Of Terminal Blocks     | 2 neutral / earth (Quick) with 22 outgoing                                                 |
| Distribution Block Outgoers   | 22 x 10 mm <sup>2</sup> for earth / neutral<br>22 x 16 mm <sup>2</sup> for earth / neutral |
| Locking Options Description   | Keylock option                                                                             |
| Enclosure Material            | Enclosure: self-extinguishing material                                                     |
| Colour                        | Enclosure: white (RAL 9003)                                                                |

### Environment

|           |                                                                     |
|-----------|---------------------------------------------------------------------|
| Standards | EN 60439-3<br>IEC 60695-2-1<br>IEC 60529<br>EN 50102<br>IEC 60439-3 |
|-----------|---------------------------------------------------------------------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                         |                                                                                                 |
|-------------------------|-------------------------------------------------------------------------------------------------|
| Fire Resistance         | Back part: 650 °C conforming to IEC 60695-2-1<br>Front face: 650 °C conforming to IEC 60695-2-1 |
| Ik Degree Of Protection | IK07 conforming to EN 50102                                                                     |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type Of Package 1       | PCE     |
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 10 cm   |
| Package 1 Width              | 25.7 cm |
| Package 1 Length             | 45 cm   |
| Package 1 Weight             | 1.7 kg  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|