Product datasheet

Specification



RS485 interface 2 wires ACE949-2 for Sepam 20, 40, 60, 80



59642

Main

Range Of Product	Sepam series 60 Sepam series 80	
	Sepam series 40	
	Sepam series 20	
	Sepam series 48	
	Sepam series 80 NPP	
Device Short Name	ACE949-2	

Complementary

Complementary	
Communication Port Protocol	Modbus RTU network: E-LAN interface: RS485 - 2-wire Modbus RTU network: S-LAN interface: RS485 - 2-wire
Local Signalling	LED for link activity (front face)
[Us] Rated Supply Voltage	12 V DC tolerance: +/- 10 % 24 V DC tolerance: +/- 10 %
Maximum Supply Current	16 mA: receiving mode 40 mA: maximum in sending mode
Mounting Mode	Fixed
Mounting Support	Symmetrical DIN rail
Height	88 mm
Width	72 mm
Depth	30 mm
Net Weight	0.1 kg
Mechanical Robustness	Earthquakes in operation (level: 2): 1 Gn (vertical axes) conforming to IEC 60255-21-3 Earthquakes in operation (level: 2): 2 Gn (horizontal axes) conforming to IEC 60255-21-3 Jolts de-energized (level: 2): 20 Gn/16 ms conforming to IEC 60255-21-2 Shocks de-energized (level: 2): 27 Gn/11 ms conforming to IEC 60255-21-2 Shocks in operation (level: 2): 10 Gn/11 ms conforming to IEC 60255-21-2 Vibrations de-energized (level: 2): 2 Gn, 10 Hz150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: 2): 1 Gn, 10 Hz150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: Fc): 2 Hz13.2 Hz, a = +/- 1 mm conforming to IEC 60068-2-6
Maximum Cable Distance Between Devices	10 Devices <180 m at 12 V DC 10 Devices <750 m at 24 V DC 20 Devices <160 m at 12 V DC 20 Devices <450 m at 24 V DC 25 Devices <125 m at 12 V DC 25 Devices <375 m at 24 V DC 5 Devices <1000 m at 24 V DC 5 Devices <300 m at 12 V DC
Auxiliary Connection Terminal	Earthing terminal: screw-type connectorcable 2.550 mm² <0.2 m Earthing terminal: screw-type connectortinned copper braid 6100 mm²

20 Apr 2024 Life Is On Schneider



Environment

Electromagnetic Compatibility

1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 1 kV DM, conforming to IEC 60255-22-1

1 MHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 2.5 kV DM, conforming to ANSI C37.90.1

100 kHz damped oscillating wave: (immunity tests-conducted disturbances), 2.5 kV CM, 1 kV DM, conforming to IEC 61000-4-12

Conducted disturbance emission: (emission tests), conforming to IEC 60255-25 Conducted disturbance emission: (emission tests), A, conforming to EN 55022 Disturbing field emission: (emission tests), conforming to IEC 60255-25 Disturbing field emission: (emission tests), A, conforming to EN 55022 Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 4 kV contact, conforming to ANSI C37.90.3

Electrostatic discharge: (immunity tests-radiated disturbances), 8 kV air, 6 kV contact, conforming to IEC 60255-22-2

Fast transient bursts: (immunity tests-conducted disturbances), 4kV, 2.5 kHz, conforming to ANSI C37.90.1

Fast transient bursts: (immunity tests-conducted disturbances), A and B, 4kV, 2.5 kHz/2 kV, 5 kHz, conforming to IEC 60255-22-4

Fast transient bursts: (immunity tests-conducted disturbances), IV, 4kV, 2.5 kHz, conforming to IEC 61000-4-4 $\,$

Immunity to conducted RF disturbances: (immunity tests-conducted disturbances), III, 10 V, conforming to IEC 60255-22-6

Immunity to magnetic fields at network frequency: (immunity tests-radiated disturbances), IV, 30 A/m (continuous)-300 A/m (1-3 s), conforming to IEC 61000-4-8 Immunity to radiated fields: (immunity tests-radiated disturbances), 10 V/m, 80 MHz... 1 GHz. conforming to IEC 60255-22-3

Immunity to radiated fields: (immunity tests-radiated disturbances), 35 V/m, 25 MHz... 1 GHz, conforming to ANSI C37.90.2

Immunity to radiated fields: (immunity tests-radiated disturbances), III, 10 V/m, 80 MHz...2 GHz, conforming to IEC 61000-4-3

Surges: (immunity tests-conducted disturbances), III, 2 kV CM, 1 kV DM, conforming to IEC 61000-4-5

Voltage interruptions: (immunity tests-conducted disturbances), 100 % during 100 ms, conforming to IEC 60255-11

Climatic Withstand

Influence of corrosion/gaz test 2 (in operation) : 21 days, 75 % RH, 25 $^{\circ}$ C, 0.5 ppm H2S, 1 ppm S02 conforming to IEC 60068-2-60

Influence of corrosion/gaz test 4 (in operation) : 21 days, 75 % RH, 25 °C, 0.01 ppm H2S, 0.2 ppm S02, 0.2 ppm NO2, 0.01 ppm Cl2 conforming to IEC 60068-2-60 Continuous exposure to damp heat (in operation) : Cab: 10 days, 93 % RH, 40 °C conforming to IEC 60068-2-78

Continuous exposure to damp heat (in storage) : Cab: 56 days, 93 % RH, 40 $^{\circ}\text{C}$ conforming to IEC 60068-2-78

Continuous exposure to damp heat (in storage) : Db: 6 days, 95 % RH, 55 $^{\circ}$ C conforming to IEC 60068-2-30

Exposure to cold (in operation): Ad: - 25 °C conforming to IEC 60068-2-1 Exposure to cold (in storage): Ab: - 25 °C conforming to IEC 60068-2-1 Exposure to dry heat (in operation): Bd: 70 °C conforming to IEC 60068-2-2 Exposure to dry heat (in storage): Bb: 70 °C conforming to IEC 60068-2-2 Salt mist (in operation): Kb/2: 6 days conforming to IEC 60068-2-52 Temperature variation with specified variation rate (in storage): Nb: - 25 °C to 70 °C.

Temperature variation with specified variation rate (in storage) : Nb: - 25 $^{\circ}\text{C}$ to 70 $^{\circ}\text{C},$ 5 $^{\circ}\text{C/min}$ conforming to IEC 60068-2-14

Ambient Air Temperature For Operation

-25...70 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.000 cm
Package 1 Width	12.100 cm
Package 1 Length	18.300 cm
Package 1 Weight	140.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	8

Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.460 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	64
Package 3 Height	30.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	25.560 kg

Sustainability Screen Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information