Product datasheet

Specification





TeSys K reversing contactor , 3P , AC-3 <= 440 V 12 A , 1 NO , 230...240 V AC

LC2K1210U7

Discontinued on: 23 Jan 2021

(!) Discontinued

Main

mani		
Range	TeSys	
Product Name	TeSys K	
Product Or Component Type	Reversing contactor	
Device Short Name	LC2K	
Device Application	Control	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-3 AC-4 AC-1	
Device Presentation	Preassembled with reversing power busbar	
Poles Description	3P	
Power Pole Contact Composition	3 NO	
[Ue] Rated Operational Voltage	Power circuit: 690 V AC 50/60 Hz Signalling circuit: <= 690 V AC 50/60 Hz	
[le] Rated Operational Current	20 A (at <50 °C) at <= 440 V AC AC-1 for power circuit 16 A (at <70 °C) at 690 V AC AC-1 for power circuit 12 A at <= 440 V AC AC-3 for power circuit	
Motor Power Kw	4 kW at 480 V AC 50/60 Hz 4 kW at 500600 V AC 50/60 Hz 4 kW at 660690 V AC 50/60 Hz 3 kW at 220230 V AC 50/60 Hz 5.5 kW at 380415 V AC 50/60 Hz 5.5 kW at 440 V AC 50/60 Hz	
Control Circuit Type	AC at 50/60 Hz	
[Uc] Control Circuit Voltage	230240 V AC 50/60 Hz	
Auxiliary Contact Composition	1 NO	
[Uimp] Rated Impulse Withstand Voltage	8 kV	
Overvoltage Category	III	
[Ith] Conventional Free Air Thermal Current	20 A (at 50 °C) for power circuit 10 A (at 50 °C) for signalling circuit	
Irms Rated Making Capacity	144 A at 690 V AC for power circuit conforming to NF C 63-110 144 A at 690 V AC for power circuit conforming to IEC 60947 110 A AC for signalling circuit conforming to IEC 60947	
Rated Breaking Capacity	110 A at 440 V conforming to IEC 60947 80 A at 500 V conforming to IEC 60947 70 A at 660690 V conforming to IEC 60947	

19 Apr 2024 Life Is On Schneider

[Icw] Rated Short-Time Withstand	115 A 50 °C - 1 s for power circuit
Current	105 A 50 °C - 5 s for power circuit
	100 A 50 °C - 10 s for power circuit
	75 A 50 °C - 30 s for power circuit
	55 A 50 °C - 1 min for power circuit
	50 A 50 °C - 3 min for power circuit
	80 A - 1 s for signalling circuit
	90 A - 500 ms for signalling circuit
	110 A - 100 ms for signalling circuit
	25 A 50 °C - >= 15 min for power circuit
	· ·· · · · · · · · · · · · · · · · · ·
Associated Fuse Rating	25 A gG at <= 440 V for power circuit
	25 A aM for power circuit
	10 A gG for signalling circuit conforming to IEC 60947
	10 A gG for signalling circuit conforming to VDE 0660
Average Impedance	3 mOhm - Ith 20 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit: 600 V conforming to UL 508
[,	Power circuit: 690 V conforming to EC 60947-4-1
	Signalling circuit: 690 V conforming to IEC 60947-4-1
	Signalling circuit: 690 V conforming to IEC 60947-5-1
	Signalling circuit: 600 V conforming to UL 508
	Power circuit: 600 V conforming to CSA C22.2 No 14
	Signalling circuit: 600 V conforming to CSA C22.2 No 14
Electrical Durability	0.3 Mcycles 20 A AC-1 at Ue <= 440 V
	1.3 Mcycles 12 A AC-3 at Ue <= 440 V
Interlocking Type	Mechanical
Mounting Support	Plate
mounting Support	Rail
Standards	EN/IEC 60947-4-1
	GB/T 14048.4
	UL 60947-4-1
	CSA C22.2 No 60947-4-1
	JIS C8201-4-1
Product Certifications	CB Scheme
Product Certifications	CCC
Product Certifications	CCC UL
Product Certifications	CCC UL CSA
Product Certifications	CCC UL CSA EAC
Product Certifications	CCC UL CSA EAC CE
Product Certifications	CCC UL CSA EAC
	CCC UL CSA EAC CE UKCA
Product Certifications Connections - Terminals	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid
	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end
	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end
	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid
	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end
Connections - Terminals	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end
	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end
Connections - Terminals	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end
Connections - Terminals Tightening Torque	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm
Connections - Terminals	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing
Connections - Terminals Tightening Torque	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm
Connections - Terminals Tightening Torque	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing
Connections - Terminals Tightening Torque Operating Time	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening
Connections - Terminals Tightening Torque Operating Time	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 200000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 200000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 5 Mcycles
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Maximum Operating Rate	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 5 Mcycles
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Maximum Operating Rate Complementary	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 5 Mcycles
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Maximum Operating Rate	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 200000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 5 Mcycles 3600 cyc/h
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Maximum Operating Rate Complementary	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 5 Mcycles
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Maximum Operating Rate Complementary	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 200000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 5 Mcycles 3600 cyc/h
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Maximum Operating Rate Complementary Control Circuit Voltage Limits	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 5 Mcycles 3600 cyc/h Operational: 0.81.15 Uc (at <50 °C) Drop-out: 0.20.75 Uc (at <50 °C)
Connections - Terminals Tightening Torque Operating Time Safety Reliability Level Mechanical Durability Maximum Operating Rate Complementary Control Circuit Voltage Limits Inrush Power In Va	CCC UL CSA EAC CE UKCA Screw clamp terminals 1 cable(s) 1.54 mm²solid Screw clamp terminals 1 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.342.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 1.54 mm²solid Screw clamp terminals 2 cable(s) 0.754 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.754 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.341.5 mm²flexible with cable end 0.81.3 N.m - on screw clamp terminals Philips No 2 0.81.3 N.m - on screw clamp terminals flat Ø 6 mm 1020 ms coil energisation and NO closing 1020 ms coil de-energisation and NO opening B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 5 Mcycles 3600 cyc/h Operational: 0.81.15 Uc (at <50 °C) Drop-out: 0.20.75 Uc (at <50 °C)

Auxiliary Contacts Type	type instantaneous 1 NO	
Signalling Circuit Frequency	<= 400 Hz	
Minimum Switching Current	5 mA for signalling circuit	
Minimum Switching Voltage	17 V for signalling circuit	
Non Overlap Distance	0.5 mm	
Insulation Resistance	> 10 MOhm for signalling circuit	

Environment

Ip Degree Of Protection	IP20 conforming to VDE 0106	
Protective Treatment	TC conforming to IEC 60068 TC conforming to DIN 50016	
Ambient Air Temperature For Operation	-2550 °C	
Ambient Air Temperature For Storage	-5080 °C	
Operating Altitude	2000 m without derating	
Flame Retardance	V1 conforming to UL 94 Requirement 2 conforming to NF F 16-101 Requirement 2 conforming to NF F 16-102	
Mechanical Robustness	Shocks contactor closed, on X axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Y axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor closed, on Z axis: 15 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on X axis: 6 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Y axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks contactor opened, on Z axis: 10 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations contactor closed: 4 Gn, 5300 Hz conforming to IEC 60068-2-6 Vibrations contactor opened: 2 Gn, 5300 Hz conforming to IEC 60068-2-6	
Height	58 mm	
Width	90 mm	
Depth	57 mm	
Net Weight	0.39 kg	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6 cm
Package 1 Width	6.2 cm
Package 1 Length	9.2 cm
Package 1 Weight	390 g

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information